

**Description**

length: 1.323", grip: 1", thread: 10-32, 100°, close tolerance bolt - reduced head short thread - cadmium plated alloy steel - tri-slot recess"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS440316
Minimum Qty (MOQ):	10
NSN:	5305-01-263-1681



## P/N NAS4403-16 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.323 Inches Nominal
<b>Fastener Length:</b>	1.308 Inches Minimum And 1.338 Inches Maximum
<b>Head Style:</b>	Pan No. 2
<b>Head Diameter:</b>	0.381 Inches Nominal
<b>Head Height:</b>	0.082 Inches Nominal
<b>Grip Diameter:</b>	0.1881 Inches Minimum And 0.1887 Inches Maximum
<b>Single Shear Strength:</b>	95000 Pounds Per Square Inch
<b>Internal Drive Style:</b>	Tri-wing Recess
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.990 Inches Minimum And 1.010 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5000 Assn Std Single Material Response Overall Or Mil-s-6049 Assn Std Single Material Response Overall Or Ams6322 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416a,ty 11,cl 3 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas4403-16 Professional/Industrial Association Specification

## How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS4403-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.