

Description

length: 1.058", grip: 0.688", thread: 1/2-28, 100°, close tolerance bolt - reduced head short thread - cadmium plated alloy steel - tri-slot recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS440411
Minimum Qty (MOQ):	10
NSN:	5305-01-259-3549



* See page 2 for technical characteristics

P/N NAS4404-11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.370 Inches Nominal
Fastener Length:	1.043 Inches Minimum And 1.073 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.456 Inches Minimum And 0.508 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.2500 Inches
Grip Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall And Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall Or Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec 1st Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas4404 Professional/industrial Association Standard

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS4404-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.