

Description

Fastener Length: 1-", Thread: 1/4-28, Thread Length: "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS440412
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-620-0230
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	136740, Meters Elec / Parts

NO IMAGE
AVAILABLE

P/N NAS4404-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.370 Inches Nominal
Fastener Length:	1.120 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.458 Inches Minimum And 0.508 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Single Shear Strength:	95000 Pounds Per Square Inch
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4340 Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000jdamil-s-6049 Mil Spec Single Material Response Or Ams 6322 National Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas 4400 Thru 4416 National Std/spec

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS4404-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.