

**Description**

Fastener Length: 1-", Thread: 1/4-28, Thread Length: "

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                             |
|-------------------------|-----------------------------|
| SKU / Model:            | NAS440412                   |
| Minimum Qty (MOQ):      | 15 EA                       |
| NSN:                    | 5305-01-620-0230            |
| Schedule B:             | 7318.15.8085                |
| ECCN:                   | EAR99                       |
| National Motor Freight: | 136740, Meters Elec / Parts |

NO IMAGE  
AVAILABLE

## P/N NAS4404-12 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.370 Inches Nominal   |
| <b>Fastener Length:</b>                               | 1.120 Inches Nominal   |
| <b>Head Style:</b>                                    | Flat Countersunk   |
| <b>Head Diameter:</b>                                 | 0.458 Inches Minimum And 0.508 Inches Maximum  |
| <b>Grip Diameter:</b>                                 | 0.2485 Inches Minimum And 0.2495 Inches Maximum  |
| <b>Single Shear Strength:</b>                         | 95000 Pounds Per Square Inch   |
| <b>Internal Drive Style:</b>                          | Tri-wing Recess  |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches   |
| <b>Grip Length:</b>                                   | 0.740 Inches Minimum And 0.760 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>                      | 28   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch  |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum   |
| <b>Material:</b>                                      | Steel Comp 4340 Or Steel Comp 8740 Overall   |
| <b>Material Document And Classification:</b>          | Mil-s-5000jdamil-s-6049 Mil Spec Single Material Response Or Ams 6322 National Spec Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unjf   |
| <b>Specification/standard Data:</b>                   | 80205-nas 4400 Thru 4416 National Std/spec   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS4404-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.