

## **P/N NAS4404-17**

### **Description**

Fastener Length: 1-7/16", Thread: 1/4-28, Thread Length: 3/8

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS440417

Minimum Qty (MOQ):

NSN: 5305-01-620-0221

Schedule B: 7318.15.8085

ECCN: EAR99









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS4404-17 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.370 Inches Nominal
Fastener Length:	1.432 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.458 Inches Minimum And 0.508 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Single Shear Strength:	95000 Pounds Per Square Inch
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.052 Inches Minimum And 1.062 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4340 Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec Single Material Response Or Mil-s-6049 Mil Spec Single Material Response Or Aams 6322 Mil Spec 6th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty Ii, Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas 4400 Thru 4416 National Std/spec

## **How to Order**

Order this close tolerance screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/close+tolerance+screws/NAS4404-17">https://military-fasteners.com/screws/close+tolerance+screws/NAS4404-17</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.