

P/N NAS4404-20

Description

Fastener Length: 1-5/8", Thread: 1/4-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS440420
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-195-8382
Schedule B:	7318.15.8085
FCCN:	9A991



^{*} See page 2 for technical characteristics

P/N NAS4404-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.355 Inches Minimum And 0.385 Inches Maximum
Fastener Length:	1.605 Inches Minimum And 1.635 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.456 Inches Minimum And 0.508 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.240 Inches Minimum And 1.260 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty li,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas4404 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/NAS4404-20 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.