

**Description**

NAS4450S05-03 Pin-Rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS4450S0503
Minimum Qty (MOQ):	5
NSN:	5320-01-056-1563
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS4450S05-03 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.445 Inches Minimum And 0.485 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.039 Inches Minimum And 0.047 Inches Maximum
<b>Width Between Flats:</b>	0.0635 Inches Minimum And 0.0645 Inches Maximum
<b>Shank Diameter:</b>	0.1625 Inches Minimum And 0.1635 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.245 Inches Minimum And 0.257 Inches Maximum
<b>Grip Length:</b>	0.178 Inches Minimum And 0.198 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Material:</b>	Steel Comp 8740 Overall Or Steel Comp E4340 Overall Or Steel Comp 4340 Overall
<b>Material Document And Classification:</b>	Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas4450 Professional/industrial Association Standard

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/NAS4450S05-03](https://military-fasteners.com/pins/pin_rivets/NAS4450S05-03) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.