

Description

length: 0.635", grip: 0.312", thread: 10-32, 100°, close tolerance bolt - short thread - corrosion resistant steel - tri-slot recess"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS45035
Minimum Qty (MOQ):	10
NSN:	5305-01-260-0833

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS4503-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.620 Inches Minimum And 0.650 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.338 Inches Minimum And 0.381 Inches Maximum
Grip Diameter:	0.188 Inches Minimum And 0.190 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec All Treatment Responses Overall
Supplementary Features:	Tri-wing Recess No. Nas4000-5,thd End Color Code Green
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas4503 Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS4503-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.