

Description

length: 0.573", grip: 0.250" length: 10-32, 100°, close tolerance bolt - short thread - corrosion resistant steel - tri-slot recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS4503U3 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-185-6285 |

NO IMAGE
AVAILABLE

P/N NAS4503U3 Specifications

| | |
|----------------------------------------------|----------------------------------------------------------------------------------------------------------|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.323 Inches Nominal |
| Fastener Length: | 0.496 Inches Minimum And 0.526 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.338 Inches Minimum And 0.381 Inches Maximum |
| Grip Diameter: | 0.1890 Inches Minimum And 0.1895 Inches Maximum |
| Internal Drive Style: | Tri-wing Recess |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.178 Inches Minimum And 0.198 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas4503 Professional/industrial Association Standard |

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS4503U3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.