

Description

length: 0.696", grip: 0.375", thread: 10-32, 100°, close tolerance bolt - short thread - corrosion resistant steel - tri-slot recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS4503U6
Minimum Qty (MOQ):	10
NSN:	5306-01-141-0121



P/N NAS4503U6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Maximum
Fastener Length:	0.698 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.381 Inches Maximum
Grip Diameter:	0.2177 Inches Minimum And 0.2182 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.375 Inches Nominal
Thread Quantity Per Inch:	32
Countersink Angle:	100.0 Degrees Nominal
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Nas4500 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Nas4003 Fed Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS4503U6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.