

Description

Fastener Length: 1-33/64", Thread: 10-32, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS4603U19
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-191-5279
Schedule B:	8108.90.3060
ECCN:	9A991



\* See page 2 for technical characteristics

## P/N NAS4603U19 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.323 Inches Maximum
<b>Fastener Length:</b>	1.496 Inches Minimum And 1.526 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.338 Inches Minimum And 0.381 Inches Maximum
<b>Grip Diameter:</b>	0.1890 Inches Minimum And 0.1895 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	1.178 Inches Minimum And 1.198 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Surface Finish:</b>	125.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Material:</b>	Titanium Alloy Overall
<b>Material Document And Classification:</b>	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas4603 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS4603U19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.