



Military-Fasteners.com

P/N NAS4603U5

Description

Fastener Length: 41/64", Thread: 10-32, Thread Length: 5/16", NAS4603 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS4603U5
Minimum Qty (MOQ):	10
NSN:	5306-01-187-9057
Schedule B:	8108.90.3060
ECCN:	EAR99



NAS4603U5



* See page 2 for technical characteristics

P/N NAS4603U5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Maximum
Fastener Length:	0.620 Inches Minimum And 0.650 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.338 Inches Minimum And 0.381 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	125.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Threads
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas4603 Professional/industrial Association Standard

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS4603U5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.