

Description

Fastener Length: 1-5/16", Thread: 1/4-28, Thread Length: "

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS4604U15
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-196-3183
Schedule B:	8108.90.3060
ECCN:	9A991



\* See page 2 for technical characteristics

## P/N NAS4604U15 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.370 Inches Nominal
<b>Fastener Length:</b>	1.293 Inches Minimum And 1.323 Inches Maximum
<b>Head Style:</b>	Pan No. 2
<b>Head Diameter:</b>	0.456 Inches Minimum And 0.508 Inches Maximum
<b>Head Height:</b>	0.111 Inches Nominal
<b>Grip Diameter:</b>	0.2490 Inches Minimum And 0.2495 Inches Maximum
<b>Internal Drive Style:</b>	Tri-wing Recess
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.928 Inches Minimum And 0.948 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 3140 Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas4600 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS4604U15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.