

P/N NAS4604U3

Description

Fastener Length: 9/16", Thread: 1/4-28, Thread Length: "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| SKU / Model: | NAS4604U3 |
|--------------------|------------------|
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5305-01-196-3184 |
| Schedule B: | 8108.90.3060 |
| FCCN: | FAR99 |



^{*} See page 2 for technical characteristics

P/N NAS4604U3 Specifications

| Thread Class: | 3a |
|------------------------------|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.370 Inches Nominal |
| Fastener Length: | 0.543 Inches Minimum And 0.573 Inches Maximum |
| Head Style: | Pan No. 2 |
| Head Diameter: | 0.456 Inches Minimum And 0.508 Inches Maximum |
| Head Height: | 0.111 Inches Nominal |
| Grip Diameter: | 0.2490 Inches Minimum And 0.2495 Inches Maximum |
| Internal Drive Style: | Tri-wing Recess |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.178 Inches Minimum And 0.198 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Steel Comp 3140 Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas4600 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS4604U3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.