

Description

Fastener Length: 9/16", Thread: 1/4-28, Thread Length: "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS4604U3
Minimum Qty (MOQ):	20 EA
NSN:	5305-01-196-3184
Schedule B:	8108.90.3060
ECCN:	EAR99



P/N NAS4604U3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.370 Inches Nominal
Fastener Length:	0.543 Inches Minimum And 0.573 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.456 Inches Minimum And 0.508 Inches Maximum
Head Height:	0.111 Inches Nominal
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp 3140 Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas4600 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS4604U3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.