

Description

Fastener Length: 1-1/4", Thread: 5/16-24, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS4605U13
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-598-1840
Schedule B:	8108.90.3060
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N NAS4605U13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Nominal
Fastener Length:	1.250 Inches Nominal
Head Style:	Countersunk Cylindrical Convex
Head Diameter:	0.575 Inches Minimum And 0.635 Inches Maximum
Head Height:	0.138 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Head Major Diameter:	0.635 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.313 Inches
Grip Length:	0.812 Inches Nominal
Thread Quantity Per Inch:	24
Countersink Angle:	101.0 Degrees Nominal
Material:	Titanium Alloy Uns R56400 Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS4605U13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.