

Description

Fastener Length: 1-37/64", Thread: 1/4-24, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS4605U18 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-01-256-5795 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS4605U18 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.438 Inches Nominal |
| Fastener Length: | 1.548 Inches Minimum And 1.578 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.575 Inches Minimum And 0.635 Inches Maximum |
| Grip Diameter: | 0.3115 Inches Minimum And 0.3120 Inches Maximum |
| Internal Drive Style: | Tri-wing Recess |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 1.115 Inches Minimum And 1.135 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Titanium Alloy Uns R56400 Overall |
| Material Document And Classification: | Ams 4928 Assn Std Single Material Response Overall And Ams 4967 Assn Std Single Material Response Overall |
| Supplementary Features: | Tri-wing Recess No. Nas4000-7 |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas4605 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS4605U18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.