

Description

Fastener Length: 1-37/64", Thread: 1/4-24, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS4605U18
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-256-5795
Schedule B:	8108.90.3060
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS4605U18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Nominal
Fastener Length:	1.548 Inches Minimum And 1.578 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.575 Inches Minimum And 0.635 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.312 Inches
Grip Length:	1.115 Inches Minimum And 1.135 Inches Maximum
Thread Quantity Per Inch:	24
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall And Ams 4967 Assn Std Single Material Response Overall
Supplementary Features:	Tri-wing Recess No. Nas4000-7
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas4605 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS4605U18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.