

Description

Nut Length: 57/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS463FC416G
Minimum Qty (MOQ):	10 EA
NSN:	5310-01-575-2751
Schedule B:	7318.16.0085
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N NAS463FC416G Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	0.891 Inches Minimum
Thru-hole Diameter:	0.270 Inches Minimum And 0.280 Inches Maximum
Plate Thickness:	0.059 Inches Minimum And 0.067 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.497 Inches Minimum And 0.503 Inches Maximum
End Item Identification:	Aft Fuselage
Part Name Assigned By Controlling Agency:	Nut Spacer Plate Plain
Special Features:	Suffix "g" Indicates 2 Coats Of Epoxy Primer Per Mil-prf-85582 Or Mil-prf-23377, Type 1, Class Optional. Dimensions Apply Prior To Primer Application
Material:	Steel Comp 321 Overall And Steel Comp 347 Overall
Surface Treatment:	Passivate Overall

How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463FC416G> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.