

**Description**

Length: 29/32

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS463FDD416M
Minimum Qty (MOQ):	50
NSN:	5310-00-595-9705
Schedule B:	7616.10.1000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS463FDD416M Specifications

<b>Mounting Hole Diameter:</b>	0.102 Inches Minimum And 0.108 Inches Maximum
<b>Nut Style:</b>	Plate Nut Spacer
<b>Nut Length:</b>	0.876 Inches Minimum And 0.906 Inches Maximum
<b>Thru-hole Diameter:</b>	0.270 Inches Minimum And 0.280 Inches Maximum
<b>Plate Thickness:</b>	0.059 Inches Minimum And 0.067 Inches Maximum
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.497 Inches Minimum And 0.503 Inches Maximum
<b>Material:</b>	Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy 7075 Overall
<b>Material Document And Classification:</b>	Qq-a-250/3,t6 Fed Spec 1st Material Response Overall Or Qq-a-250/5,t3 Or T4 Fed Spec 2nd Material Response Overall Or Qq-a-250/13,t6 Fed Spec 3rd Material Response Overall
<b>Specification/standard Data:</b>	80205-nas463 Professional/Industrial Association Standard

## How to Order

Order this spacer from our inventory online by visiting <https://military-fasteners.com/spacers/spacers/NAS463FDD416M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.