

Description

Nut Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS463FKD10
Minimum Qty (MOQ):	10 EA
NSN:	5310-01-066-3540
Schedule B:	7616.10.1000
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N NAS463FKD10 Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	0.688 Inches Nominal
Thru-hole Diameter:	0.210 Inches Minimum And 0.220 Inches Maximum
Plate Thickness:	0.063 Inches Nominal
Nut Mounting Provision:	Countersunk Holes
Mounting Provision Location:	Nut Projection Side
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.341 Inches Minimum And 0.347 Inches Maximum
Mounting Hole Countersink Angle:	100.0 Degrees Nominal
iii Part Name Assigned By Controlling Agency:	Navy Special Project
Material:	Aluminum Alloy 5052 Overall
Material Document And Classification:	Qq-a-250/8,h32 Fed Spec Single Material Response Overall Or Qq-a-250/8,h34 Fed Spec Single Material Response Overall Or Qq-a-250/8 H36 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas463 Professional/industrial Association Standard

How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463FKD10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.