

Description

Nut Length: 45/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS463FKDD10
Minimum Qty (MOQ):	60 EA
NSN:	5310-00-595-9699
Schedule B:	7616.10.1000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS463FKDD10 Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	0.673 Inches Minimum And 0.703 Inches Maximum
Thru-hole Diameter:	0.210 Inches Minimum And 0.220 Inches Maximum
Plate Thickness:	0.059 Inches Minimum And 0.067 Inches Maximum
Nut Mounting Provision:	Countersunk Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.341 Inches Minimum And 0.347 Inches Maximum
Mounting Hole Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-250/3,t6 Fed Spec 1st Material Response Overall Or Qq-a-250/5,t3 Or T4 Fed Spec 2nd Material Response Overall Or Qq-a-250/13,t6 Fed Spec 3rd Material Response Overall
Specification/standard Data:	80205-nas463 Professional/industrial Association Standard

How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463FKDD10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.