

Description

Nut Length: 1-1/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS463TC10L |
| Minimum Qty (MOQ): | 100 EA |
| NSN: | 5310-01-197-3574 |
| Schedule B: | 7318.16.0085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS463TC10L Specifications

| | |
|---|--|
| Mounting Hole Diameter: | 0.102 Inches Minimum And 0.108 Inches Maximum |
| Nut Style: | Plate Nut Spacer |
| Nut Length: | 1.078 Inches Nominal |
| Thru-hole Diameter: | 0.210 Inches Minimum And 0.220 Inches Maximum |
| Plate Thickness: | 0.011 Inches Minimum And 0.021 Inches Maximum |
| Plate Width: | 0.500 Inches Nominal |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.341 Inches Minimum And 0.347 Inches Maximum |
| Center To Center Distance Between Mounting Holes Along Length: | 0.310 Inches Minimum And 0.314 Inches Maximum |
| Material: | Steel Comp 301 Overall Or Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Comp 321 Overall Or Steel Comp 347 Overall |
| Material Document And Classification: | Mil-s-5059 Mil Spec 1st Material Response Overall Or Mil-s-5059 Mil Spec 2nd Material Response Overall Or Mil-s-5059 Mil Spec 3rd Material Response Overall Or Mil-s-5059 Mil Spec 4th Material Response Overall Or Ams 5510 Assn Std 5th Material Response Overall Or Ams 5512 Assn Std 6th Material Response Overall |

How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463TC10L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.