

P/N NAS463TC416

Description

Nut Length: 1-5/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS463TC416

Minimum Qty (MOQ): 20 EA

NSN: 5310-01-085-9935

Schedule B: 7318.16.0085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS463TC416 Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	1.063 Inches Minimum And 1.093 Inches Maximum
Thru-hole Diameter:	0.250 Inches Nominal
Plate Thickness:	0.058 Inches Minimum And 0.068 Inches Maximum
Plate Width:	0.470 Inches Minimum And 0.530 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.341 Inches Minimum And 0.347 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.310 Inches Minimum And 0.314 Inches Maximum
Material:	Steel Comp 301 Overall Or Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Comp 347 Overall Or Steel Comp 348 Overall
Material Document And Classification:	Mil-s-5059 Mil Spec 1st Material Response Overall Or Mil-s-5059 Mil Spec 2nd Material Response Overall Or Mil-s-5049 Mil Spec 3rd Material Response Overall Or Mil-s-5059 Mil Spec 4th Material Response Overall Or Mil-s-6721 Mil Spec 5th Material Response Overall Or Mil-s-6721 Mil Spec 6th Material Response Overall
Specification/standard Data:	80205-nas463 Professional/industrial Association Standard

How to Order

Order this nut spacer from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS463TC416 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.