

Description

Nut Length: 1-5/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------|
| SKU / Model: | NAS463TDD10 |
| Minimum Qty (MOQ): | 30 EA |
| NSN: | 5310-00-208-1762 |
| Schedule B: | 7616.10.1000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013540, Alum Nuts |

NO IMAGE
AVAILABLE

P/N NAS463TDD10 Specifications

| | |
|---|--|
| Mounting Hole Diameter: | 0.102 Inches Minimum And 0.108 Inches Maximum |
| Nut Style: | Plate Nut Spacer |
| Nut Length: | 1.063 Inches Minimum And 1.093 Inches Maximum |
| Thru-hole Diameter: | 0.210 Inches Minimum And 0.220 Inches Maximum |
| Plate Thickness: | 0.059 Inches Minimum And 0.067 Inches Maximum |
| Plate Width: | 0.485 Inches Minimum And 0.515 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.341 Inches Minimum And 0.347 Inches Maximum |
| Center To Center Distance Between Mounting Holes Along Length: | 0.310 Inches Minimum And 0.314 Inches Maximum |
| Material: | Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy 7075 Overall |
| Material Document And Classification: | Qq-a-250/3,alloy 2014,t6 Fed Spec 1st Material Response Overall Or Qq-a-250/5 Alloy Alclad 2024,t3 Fed Spec 2nd Material Response Overall Or Qq-a-250/5,t4 Fed Spec 3rd Material Response Overall Or Qq-b-250/13,t6 Fed Spec 4th Material Response Overall |
| Specification/standard Data: | 80205-nas463 Professional/industrial Association Standard |

How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463TDD10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.