

Description

Nut Length: 1-5/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS463TDD10H
Minimum Qty (MOQ):	75 EA
NSN:	5310-00-944-5981
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS463TDD10H Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	1.063 Inches Minimum And 1.093 Inches Maximum
Thru-hole Diameter:	0.210 Inches Minimum And 0.220 Inches Maximum
Plate Thickness:	0.075 Inches Minimum And 0.105 Inches Maximum
Plate Width:	0.500 Inches Nominal
Nut Mounting Provision:	Countersunk Holes
Mounting Provision Location:	Nut Projection Side
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.341 Inches Minimum And 0.347 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.310 Inches Minimum And 0.314 Inches Maximum
Mounting Hole Countersink Angle:	100.0 Degrees Nominal
Special Features:	Aluminum Cladding
Material:	Aluminum Alloy Overall

How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463TDD10H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.