

Description

Nut Length: 1-5/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS463TDD10H |
| Minimum Qty (MOQ): | 75 EA |
| NSN: | 5310-00-944-5981 |
| Schedule B: | 7616.10.1000 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS463TDD10H Specifications

| | |
|---|---|
| Mounting Hole Diameter: | 0.102 Inches Minimum And 0.108 Inches Maximum |
| Nut Style: | Plate Nut Spacer |
| Nut Length: | 1.063 Inches Minimum And 1.093 Inches Maximum |
| Thru-hole Diameter: | 0.210 Inches Minimum And 0.220 Inches Maximum |
| Plate Thickness: | 0.075 Inches Minimum And 0.105 Inches Maximum |
| Plate Width: | 0.500 Inches Nominal |
| Nut Mounting Provision: | Countersunk Holes |
| Mounting Provision Location: | Nut Projection Side |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.341 Inches Minimum And 0.347 Inches Maximum |
| Center To Center Distance Between Mounting Holes Along Length: | 0.310 Inches Minimum And 0.314 Inches Maximum |
| Mounting Hole Countersink Angle: | 100.0 Degrees Nominal |
| Special Features: | Aluminum Cladding |
| Material: | Aluminum Alloy Overall |

How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463TDD10H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.