

Description

Nut Length: 1-5/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS463TDD416
Minimum Qty (MOQ):	30 EA
NSN:	5310-00-595-9706
Schedule B:	7616.10.1000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts

NO IMAGE
AVAILABLE

P/N NAS463TDD416 Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	1.063 Inches Minimum And 1.093 Inches Maximum
Thru-hole Diameter:	0.270 Inches Minimum And 0.280 Inches Maximum
Plate Thickness:	0.059 Inches Minimum And 0.067 Inches Maximum
Plate Width:	0.485 Inches Minimum And 0.515 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.341 Inches Minimum And 0.347 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.310 Inches Minimum And 0.314 Inches Maximum
Material:	Aluminum Alloy 2024 Overall Or Aluminum Alloy 7075 Overall

How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463TDD416> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.