



Military-Fasteners.com

P/N NAS463WC10L

Description

Nut Length: 31/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS463WC10L
Minimum Qty (MOQ):	25 EA
NSN:	5310-01-328-1554
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS463WC10L Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	0.969 Inches Nominal
Thru-hole Diameter:	0.210 Inches Minimum And 0.220 Inches Maximum
Plate Thickness:	0.016 Inches Nominal
Plate Width:	0.391 Inches Nominal
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.341 Inches Minimum And 0.347 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.685 Inches Minimum And 0.690 Inches Maximum
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 5510 Assn Std Single Material Response Overall Or Ams 5512 Assn Std Single Material Response Overall Or Mil-s-5059 Mil Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas463 Professional/industrial Association Standard

How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463WC10L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.