

P/N NAS463WD416

Description

Nut Length: 1-1/4"

Order this part online

Additional Information

SKU / Model: NAS463WD416

Minimum Qty (MOQ): 35 EA

NSN: 5310-00-840-7465

Schedule B: 7616.10.1000

ECCN: 9A991

National Motor Freight: 013540, Alum Nuts



^{*} Manufacturer certifications are shipped with your order EREE of charge

^{*} See page 2 for technical characteristics

P/N NAS463WD416 Specifications

Mounting Hole Diameter: 0.102 Inches Minimum And 0.108 Inches Maximum Nut Style: Plate Nut Spacer Nut Length: 1.281 Inches Nominal Thru-hole Diameter: 0.270 Inches Minimum And 0.280 Inches Maximum Plate Thickness: 0.663 Inches Nominal Plate Width: 0.500 Inches Nominal Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.497 Inches Minimum And 0.503 Inches Maximum Center To Center Distance Between Mounting Hole Arrangement: 0.998 Inches Minimum And 1.002 Inches Maximum Special Features: Dyed Orange Material: Aluminum Alloy 5052 Overall Material Document And Classification: Qn-a-318, alloy 5052, temper H32 Fed Spec 1st Material Response Overall Or Qq-a-318, h34 Fed Spec 2nd Material Response Overall Or Qq-a-318, h36 Fed Spec 2nd Material Response Overall Or Qq-a-318, h36 Fed Spec 3nd Material Response Overall Or Qq-a-318, h36 Fed Spec 3nd Material Response Overall Surface Treatment: Anodize Overall Surface Treatment Document And Classification: Mil-a-8625, type 2, class 2 Mil Spec Single Treatment Response Overall Specification/standard Data: 80205-nas463 Professional/industrial Association Standard <th></th> <th></th>		
Nut Length: 1.281 Inches Nominal Thru-hole Diameter: 0.270 Inches Minimum And 0.280 Inches Maximum Plate Thickness: 0.063 Inches Nominal Plate Width: 0.500 Inches Nominal Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.497 Inches Minimum And 0.503 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: Special Features: Dyed Orange Material: Aluminum Alloy 5052 Overall Material Document And Classification: Qq-a-318,alloy 5052,temper H32 Fed Spec 1st Material Response Overall Or Qq-a-318,h34 Fed Spec 2nd Material Surface Treatment: Anodize Overall Surface Treatment Document And Classification: Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall	Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Thru-hole Diameter: 0.270 Inches Minimum And 0.280 Inches Maximum Plate Thickness: 0.063 Inches Nominal Plate Width: 0.500 Inches Nominal Nut Mounting Provision: Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: Center To Center Distance Between Mounting Holes Along Length: Special Features: Dyed Orange Material: Material Document And Classification: Qq-a-318,alloy 5052,temper H32 Fed Spec 3rd Material Response Overall Or Qq-a-318,h34 Fed Spec 2nd Material Response Overall Surface Treatment: Anodize Overall Surface Treatment Document And Classification: Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall	Nut Style:	Plate Nut Spacer
Plate Thickness: 0.063 Inches Nominal Plate Width: 0.500 Inches Nominal Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.497 Inches Minimum And 0.503 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Special Features: Dyed Orange Material: Aluminum Alloy 5052 Overall Material Document And Classification: Qq-a-318,alloy 5052,temper H32 Fed Spec 1st Material Response Overall Or Qq-a-318,h34 Fed Spec 2nd Material Response Overall Or Qq-a-318,h36 Fed Spec 3rd Material Response Overall Surface Treatment: Anodize Overall Surface Treatment Document And Classification: Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall	Nut Length:	1.281 Inches Nominal
Plate Width:0.500 Inches NominalNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.497 Inches Minimum And 0.503 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.998 Inches Minimum And 1.002 Inches MaximumSpecial Features:Dyed OrangeMaterial:Aluminum Alloy 5052 OverallMaterial Document And Classification:Qq-a-318,alloy 5052,temper H32 Fed Spec 1st Material Response Overall Or Qq-a-318,h34 Fed Spec 2nd Material Response OverallSurface Treatment:Anodize OverallSurface Treatment Document And Classification:Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall	Thru-hole Diameter:	0.270 Inches Minimum And 0.280 Inches Maximum
Nut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.497 Inches Minimum And 0.503 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.998 Inches Minimum And 1.002 Inches MaximumSpecial Features:Dyed OrangeMaterial:Aluminum Alloy 5052 OverallMaterial Document And Classification:Qq-a-318,alloy 5052,temper H32 Fed Spec 1st Material Response Overall Or Qq-a-318,h34 Fed Spec 2nd Material Response Overall Or Qq-a-318,h36 Fed Spec 3rd Material Response OverallSurface Treatment:Anodize OverallSurface Treatment Document And Classification:Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall	Plate Thickness:	0.063 Inches Nominal
Mounting Hole Arrangement Style: Distance From Aperture Center To Mounting Hole Center: 0.497 Inches Minimum And 0.503 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: Special Features: Dyed Orange Material: Aluminum Alloy 5052 Overall Material Document And Classification: Qq-a-318,alloy 5052,temper H32 Fed Spec 1st Material Response Overall Or Qq-a-318,h34 Fed Spec 2nd Material Response Overall Or Qq-a-318,h36 Fed Spec 3rd Material Response Overall Surface Treatment: Anodize Overall Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall	Plate Width:	0.500 Inches Nominal
Distance From Aperture Center To Mounting Hole Center: Center To Center Distance Between Mounting Holes Along Length: Special Features: Material: Material Document And Classification: Dyed Orange Qq-a-318,alloy 5052 Overall Qq-a-318,h36 Fed Spec 1st Material Response Overall Or Qq-a-318,h34 Fed Spec 2nd Material Response Overall Anodize Overall Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall	Nut Mounting Provision:	Straight Holes
Center To Center Distance Between Mounting Holes Along Length: Special Features: Dyed Orange Material: Material Document And Classification: Qq-a-318,alloy 5052,temper H32 Fed Spec 1st Material Response Overall Or Qq-a-318,h34 Fed Spec 2nd Material Response Overall Or Qq-a-318,h36 Fed Spec 3rd Material Response Overall Surface Treatment: Anodize Overall Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall	Mounting Hole Arrangement Style:	2 Holes
Along Length: Special Features: Dyed Orange Material: Aluminum Alloy 5052 Overall Qq-a-318,alloy 5052,temper H32 Fed Spec 1st Material Response Overall Or Qq-a-318,h34 Fed Spec 2nd Material Response Overall Or Qq-a-318,h34 Fed Spec 2nd Material Response Overall Or Qq-a-318,h36 Fed Spec 3rd Material Response Overall Surface Treatment: Anodize Overall Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall		0.497 Inches Minimum And 0.503 Inches Maximum
Material:Aluminum Alloy 5052 OverallMaterial Document And Classification:Qq-a-318,alloy 5052,temper H32 Fed Spec 1st Material Response Overall Or Qq-a-318,h34 Fed Spec 2nd Material Response Overall Or Qq-a-318,h36 Fed Spec 3rd Material Response OverallSurface Treatment:Anodize OverallSurface Treatment Document And Classification:Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall	_	0.998 Inches Minimum And 1.002 Inches Maximum
Material Document And Classification: Qq-a-318,alloy 5052,temper H32 Fed Spec 1st Material Response Overall Or Qq-a-318,h34 Fed Spec 2nd Material Response Overall Or Qq-a-318,h36 Fed Spec 3rd Material Response Overall Surface Treatment Document And Classification: Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall	Special Features:	Dyed Orange
Response Overall Or Qq-a-318,h36 Fed Spec 3rd Material Response Overall Surface Treatment: Anodize Overall Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall	Material:	Aluminum Alloy 5052 Overall
Surface Treatment Document And Classification: Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall	Material Document And Classification:	
	Surface Treatment:	Anodize Overall
Specification/standard Data: 80205-nas463 Professional/industrial Association Standard	Surface Treatment Document And Classification:	Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall
	Specification/standard Data:	80205-nas463 Professional/industrial Association Standard

How to Order

Order this nut spacer from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS463WD416 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS463WD416 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS463WD416 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/nas463WD416 and selecting the quantity you want https://military-fasteners.com/bolts/nas463WD416 and selecting the quantity you want https://military-fasteners.com/bolts/nas463WD416 and selecting the quantity you want https://military-fasteners.com/bolts/nas463WD416 and selecting the property of the property of