

Description

Nut Length: 63/64", nut spacer,

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------|
| SKU / Model: | NAS463WDD10L |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5310-00-595-9694 |
| Schedule B: | 7616.10.1000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013540, Alum Nuts |



* See page 2 for technical characteristics

P/N NAS463WDD10L Specifications

| | |
|---|---|
| Mounting Hole Diameter: | 0.102 Inches Minimum And 0.108 Inches Maximum |
| Nut Style: | Plate Nut Spacer |
| Nut Length: | 0.954 Inches Minimum And 0.984 Inches Maximum |
| Thru-hole Diameter: | 0.210 Inches Minimum And 0.220 Inches Maximum |
| Plate Thickness: | 0.012 Inches Minimum And 0.020 Inches Maximum |
| Plate Width: | 0.376 Inches Minimum And 0.406 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.341 Inches Minimum And 0.347 Inches Maximum |
| Center To Center Distance Between Mounting Holes Along Length: | 0.686 Inches Minimum And 0.690 Inches Maximum |
| Material: | Aluminum Alloy Overall |

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS463WDD10L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.