

Description

Nut Length: 1-1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS463WKDD516H
Minimum Qty (MOQ):	15 EA
NSN:	5310-00-655-9770
Schedule B:	7616.10.1000
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N NAS463WKDD516H Specifications

Mounting Hole Diameter:	0.134 Inches Minimum And 0.140 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	1.281 Inches Nominal
Thru-hole Diameter:	0.330 Inches Minimum And 0.340 Inches Maximum
Plate Thickness:	0.090 Inches Nominal
Plate Width:	0.516 Inches Nominal
Nut Mounting Provision:	Countersunk Holes
Mounting Provision Location:	Opposite Nut Projection Side
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.497 Inches Minimum And 0.503 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.998 Inches Minimum And 1.002 Inches Maximum
Mounting Hole Countersink Angle:	100.0 Degrees Nominal
Special Features:	Dyed Orange
Material:	Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-250/3,alloy 2014,temper T6 Fed Spec 1st Material Response Overall Or Qq-a-250/5,alloy 2024,temper T3 Fed Spec 2nd Material Response Overall Or Qq-a-250/5,t42 Fed Spec 3rd Material Response Overall Or Qq-a-250/13,alloy 7075,temper T6 Fed Spec 4th Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas463 Professional/industrial Association Standard

How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463WKDD516H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.