

Description

Nut Length: 63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS463XC10H
Minimum Qty (MOQ):	45 EA
NSN:	5310-00-550-4712
Schedule B:	7318.16.0085
ECCN:	9A991.
National Motor Freight:	013540, Alum Nuts



* See page 2 for technical characteristics

P/N NAS463XC10H Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	0.954 Inches Minimum And 0.984 Inches Maximum
Thru-hole Diameter:	0.260 Inches Minimum And 0.270 Inches Maximum
Plate Thickness:	0.085 Inches Minimum And 0.095 Inches Maximum
Plate Width:	0.391 Inches Minimum And 0.421 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.341 Inches Minimum And 0.347 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.686 Inches Minimum And 0.690 Inches Maximum
Material:	Steel Corrosion Resisting Overall Or Steel Comp 301 Overall Or Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall
Material Document And Classification:	Mil-s-6721 Mil Spec 1st Material Response Overall Or Mil-s-5059 Mil Spec 2nd Material Response Overall
Specification/standard Data:	80205-nas463 Professional/industrial Association Standard

How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463XC10H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.