

P/N NAS463XC10M

Description

Nut Length: 31/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS463XC10M

Minimum Qty (MOQ): 75 EA

NSN: 5310-00-558-2859

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS463XC10M Specifications

Mounting Hole Diameter:	0.134 Inches Minimum And 0.140 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	0.969 Inches Nominal
Thru-hole Diameter:	0.260 Inches Minimum And 0.270 Inches Maximum
Plate Thickness:	0.032 Inches Nominal
Plate Width:	0.406 Inches Nominal
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.341 Inches Minimum And 0.347 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.686 Inches Minimum And 0.690 Inches Maximum
Material:	Steel Comp 301 Overall Or Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall
Material Document And Classification:	Mil-s-5059 Mil Spec All Material Responses Overall
Surface Treatment:	Passivate Overall

How to Order

Order this nut spacer from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS463XC10M and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS463XC10M and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS463XC10M and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS463XC10M and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/nas463XC10M and selecting the property of the