

Description

Nut Length: 1-9/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS463XC416L
Minimum Qty (MOQ):	35 EA
NSN:	5310-00-243-2249
Schedule B:	7318.16.0085
ECCN:	9A991.
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS463XC416L Specifications

Mounting Hole Diameter:	0.198 Inches Minimum And 0.208 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	1.266 Inches Minimum And 1.296 Inches Maximum
Thru-hole Diameter:	0.322 Inches Minimum And 0.332 Inches Maximum
Plate Thickness:	0.011 Inches Minimum And 0.021 Inches Maximum
Plate Width:	0.485 Inches Minimum And 0.515 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.497 Inches Minimum And 0.503 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.998 Inches Minimum And 1.002 Inches Maximum
Material:	Steel Comp 301 Overall Or Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall
Material Document And Classification:	Mil-s-6721 Mil Spec All Material Responses Overall Or Mil-s-5059 Mil Spec All Material Responses Overall
Specification/standard Data:	80205-nas463 Professional/industrial Association Standard

How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463XC416L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.