

P/N NAS463XC416M

Description

Nut Length: 1-1/4"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | NAS463XC416M |
|-------------------------|-------------------|
| Minimum Qty (MOQ): | 30 EA |
| NSN: | 5310-00-878-6468 |
| Schedule B: | 7318.16.0085 |
| ECCN: | 9A991. |
| National Motor Freight: | 013540, Alum Nuts |



^{*} See page 2 for technical characteristics

P/N NAS463XC416M Specifications

| Mounting Hole Diameter: | 0.105 Inches Nominal |
|--|-----------------------------------|
| Nut Style: | Plate Nut Spacer |
| Nut Length: | 1.281 Inches Nominal |
| Thru-hole Diameter: | 0.322 Inches Nominal |
| Plate Thickness: | 0.032 Inches Nominal |
| Plate Width: | 0.500 Inches Nominal |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.500 Inches Nominal |
| Center To Center Distance Between Mounting Holes Along Length: | 1.000 Inches Nominal |
| Material: | Steel Corrosion Resisting Overall |
| Surface Treatment: | Passivate Overall |

How to Order

Order this nut spacer from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS463XC416M and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS463XC416M and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS463XC416M and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/nas463XC416M and selecting the quantity you want https://military-fasteners.com/bolts/nas463XC416M and selecting the quantity you want https://military-fasteners.com/bolts/nas463XC416M and selecting the quantity you want https://military-fasteners.com/bolts/nas463XC416M and selecting the property of th