



Military-Fasteners.com

P/N NAS463XC516M

Description

Nut Length: 1-9/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS463XC516M
Minimum Qty (MOQ):	40 EA
NSN:	5310-01-008-1117
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS463XC516M Specifications

Mounting Hole Diameter:	0.134 Inches Minimum And 0.140 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	1.266 Inches Minimum And 1.296 Inches Maximum
Thru-hole Diameter:	0.385 Inches Minimum And 0.395 Inches Maximum
Plate Thickness:	0.027 Inches Minimum And 0.037 Inches Maximum
Plate Width:	0.579 Inches Minimum And 0.609 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.497 Inches Minimum And 0.503 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.998 Inches Minimum And 1.002 Inches Maximum
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Mil-s-5059 Mil Spec Single Material Response Overall
Specification/standard Data:	80205-nas463 Professional/industrial Association Standard

How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463XC516M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.