

## **P/N NAS463XD10**

## **Description**

Nut Length: 63/64"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS463XD10

Minimum Qty (MOQ): 50 EA

NSN: 5310-00-543-5018

Schedule B: 7616.10.1000

ECCN: 9A991.

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS463XD10 Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	0.954 Inches Minimum And 0.984 Inches Maximum
Thru-hole Diameter:	0.260 Inches Minimum And 0.270 Inches Maximum
Plate Thickness:	0.059 Inches Minimum And 0.067 Inches Maximum
Plate Width:	0.391 Inches Minimum And 0.421 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.341 Inches Minimum And 0.347 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.686 Inches Minimum And 0.690 Inches Maximum
Material:	Aluminum Alloy 5052 Overall
Material Document And Classification:	Qq-a-250/8 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas463 Professional/industrial Association Standard

### **How to Order**

Order this nut spacer from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/NAS463XD10">https://military-fasteners.com/bolts/machine+bolts/NAS463XD10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.