

**Description**

Nut Length: 1-1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS463XD616H
Minimum Qty (MOQ):	20 EA
NSN:	5310-00-395-3312
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	013540, Alum Nuts

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS463XD616H Specifications

<b>Mounting Hole Diameter:</b>	0.134 Inches Minimum And 0.140 Inches Maximum
<b>Nut Style:</b>	Plate Nut Spacer
<b>Nut Length:</b>	1.281 Inches Nominal
<b>Thru-hole Diameter:</b>	0.448 Inches Minimum And 0.458 Inches Maximum
<b>Plate Thickness:</b>	0.090 Inches Nominal
<b>Plate Width:</b>	0.625 Inches Nominal
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.497 Inches Minimum And 0.503 Inches Maximum
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	0.998 Inches Minimum And 1.002 Inches Maximum
<b>Special Features:</b>	Dyed Orange
<b>Material:</b>	Aluminum Alloy 5052 Overall
<b>Material Document And Classification:</b>	Qq-a-250/8,alloy 5052,temper H32 Fed Spec 1st Material Response Overall Or Qq-a-250/8,h34 Fed Spec 2nd Material Response Overall Or Qq-a-250/8,h36 Fed Spec 3rd Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas463 Professional/industrial Association Standard

## How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463XD616H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.