

Description

Nut Length: 1-1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS463XD616H
Minimum Qty (MOQ):	20 EA
NSN:	5310-00-395-3312
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	013540, Alum Nuts



* See page 2 for technical characteristics

P/N NAS463XD616H Specifications

Mounting Hole Diameter:	0.134 Inches Minimum And 0.140 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	1.281 Inches Nominal
Thru-hole Diameter:	0.448 Inches Minimum And 0.458 Inches Maximum
Plate Thickness:	0.090 Inches Nominal
Plate Width:	0.625 Inches Nominal
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.497 Inches Minimum And 0.503 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.998 Inches Minimum And 1.002 Inches Maximum
Special Features:	Dyed Orange
Material:	Aluminum Alloy 5052 Overall
Material Document And Classification:	Qq-a-250/8,alloy 5052,temper H32 Fed Spec 1st Material Response Overall Or Qq-a-250/8,h34 Fed Spec 2nd Material Response Overall Or Qq-a-250/8,h36 Fed Spec 3rd Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas463 Professional/industrial Association Standard

How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463XD616H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.