

P/N NAS463XDD10

Description

Length: 63/64", nut spacer, NAS463 series washer

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS463XDD10

Minimum Qty (MOQ): 100

NSN: 5310-00-527-4477

Schedule B: 7616.10.1000

ECCN: EAR99

National Motor Freight: 013540, Alum Nuts



^{*} See page 2 for technical characteristics

P/N NAS463XDD10 Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	0.954 Inches Minimum And 0.984 Inches Maximum
Thru-hole Diameter:	0.260 Inches Minimum And 0.270 Inches Maximum
Plate Thickness:	0.058 Inches Minimum And 0.068 Inches Maximum
Plate Width:	0.391 Inches Minimum And 0.421 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.341 Inches Minimum And 0.347 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.686 Inches Minimum And 0.690 Inches Maximum
Material:	Aluminum Alloy 2014 Overall Or Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-250/3 Fed Spec 1st Material Response Overall Or Qq-a-250/13 Fed Spec 2nd Material Response Overall
Specification/standard Data:	80205-nas463 Professional/industrial Association Standard

How to Order

Order this spacer from our inventory online by visiting https://military-fasteners.com/spacers/NAS463XDD10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/spacers/NAS463XDD10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/spacers/NAS463XDD10 and selecting the quantity you want then click "add to cart".