

Description

Length: 63/64", nut spacer, NAS463 series washer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS463XDD10
Minimum Qty (MOQ):	100
NSN:	5310-00-527-4477
Schedule B:	7616.10.1000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



\* See page 2 for technical characteristics

## P/N NAS463XDD10 Specifications

<b>Mounting Hole Diameter:</b>	0.102 Inches Minimum And 0.108 Inches Maximum
<b>Nut Style:</b>	Plate Nut Spacer
<b>Nut Length:</b>	0.954 Inches Minimum And 0.984 Inches Maximum
<b>Thru-hole Diameter:</b>	0.260 Inches Minimum And 0.270 Inches Maximum
<b>Plate Thickness:</b>	0.058 Inches Minimum And 0.068 Inches Maximum
<b>Plate Width:</b>	0.391 Inches Minimum And 0.421 Inches Maximum
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.341 Inches Minimum And 0.347 Inches Maximum
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	0.686 Inches Minimum And 0.690 Inches Maximum
<b>Material:</b>	Aluminum Alloy 2014 Overall Or Aluminum Alloy 7075 Overall
<b>Material Document And Classification:</b>	Qq-a-250/3 Fed Spec 1st Material Response Overall Or Qq-a-250/13 Fed Spec 2nd Material Response Overall
<b>Specification/standard Data:</b>	80205-nas463 Professional/industrial Association Standard

## How to Order

Order this spacer from our inventory online by visiting <https://military-fasteners.com/spacers/spacers/NAS463XDD10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.