

Description

Nut Length: 63/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS463XDD10M
Minimum Qty (MOQ):	100
NSN:	5310-00-550-4719
Schedule B:	7616.10.1000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



\* See page 2 for technical characteristics

# P/N NAS463XDD10M Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	0.954 Inches Minimum And 0.984 Inches Maximum
Thru-hole Diameter:	0.260 Inches Minimum And 0.270 Inches Maximum
Plate Thickness:	0.028 Inches Minimum And 0.036 Inches Maximum
Plate Width:	0.391 Inches Minimum And 0.421 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.341 Inches Minimum And 0.347 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.686 Inches Minimum And 0.690 Inches Maximum
Material:	Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-250/3,alloy 2014,t6 Fed Spec 1st Material Response Overall Or Qq-a-250/5,alloy Alclad 2024,t3 Fed Spec 2nd Material Response Overall Or Qq-a-250/13,alloy Alclad 7075,t6 Fed Spec 3rd Material Response Overall
Specification/standard Data:	80205-nas463 Professional/industrial Association Standard

## How to Order

Order this plain nut spacer from our inventory online by visiting <https://military-fasteners.com/spacers/spacers/NAS463XDD10M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.