

Description

Nut Length: 31/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------|
| SKU / Model: | NAS463XKD10 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5310-00-006-8269 |
| Schedule B: | 7616.10.1000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013540, Alum Nuts |

NO IMAGE
AVAILABLE

P/N NAS463XKD10 Specifications

| | |
|---|--|
| Mounting Hole Diameter: | 0.102 Inches Minimum And 0.108 Inches Maximum |
| Nut Style: | Plate Nut Spacer |
| Nut Length: | 0.969 Inches Nominal |
| Thru-hole Diameter: | 0.260 Inches Minimum And 0.270 Inches Maximum |
| Plate Thickness: | 0.063 Inches Nominal |
| Plate Width: | 0.406 Inches Nominal |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.341 Inches Minimum And 0.347 Inches Maximum |
| Center To Center Distance Between Mounting Holes Along Length: | 0.686 Inches Minimum And 0.690 Inches Maximum |
| Special Features: | Dyed Orange |
| Material: | Aluminum Alloy 5052 Overall |
| Material Document And Classification: | Qq-a-250/8,alloy 5052,temper H32 Or H34 Or H36 Fed Spec All Material Responses Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas463 Professional/industrial Association Standard |

How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463XKD10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.