

P/N NAS463XKD10H

Description

Nut Length: 63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| SKU / Model: | NAS463XKD10H |
|-------------------------|-------------------|
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5310-00-721-7734 |
| Schedule B: | 7616.10.1000 |
| ECCN: | 9A991 |
| National Motor Freight: | 013540, Alum Nuts |



^{*} See page 2 for technical characteristics

P/N NAS463XKD10H Specifications

| Mounting Hole Diameter: | 0.102 Inches Minimum And 0.108 Inches Maximum |
|--|--|
| Nut Style: | Plate Nut Spacer |
| Nut Length: | 0.954 Inches Minimum And 0.984 Inches Maximum |
| Thru-hole Diameter: | 0.260 Inches Minimum And 0.270 Inches Maximum |
| Plate Thickness: | 0.086 Inches Minimum And 0.094 Inches Maximum |
| Plate Width: | 0.391 Inches Minimum And 0.421 Inches Maximum |
| Nut Mounting Provision: | Countersunk Holes |
| Mounting Provision Location: | Nut Projection Side |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.341 Inches Minimum And 0.347 Inches Maximum |
| Center To Center Distance Between Mounting Holes Along Length: | 0.686 Inches Minimum And 0.690 Inches Maximum |
| Mounting Hole Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Aluminum Alloy 5052 Overall |
| Material Document And Classification: | Qq-a-318 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall |

How to Order

Order this nut spacer from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS463XKD10H and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.