

Description

Nut Length: 31/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS463XKDD10M
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-427-1113
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS463XKDD10M Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	0.969 Inches Nominal
Thru-hole Diameter:	0.260 Inches Minimum And 0.270 Inches Maximum
Plate Thickness:	0.032 Inches Nominal
Plate Width:	0.406 Inches Nominal
Nut Mounting Provision:	Dimpled Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.341 Inches Minimum And 0.347 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.688 Inches Nominal
Material:	Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy 7075 Overall
Specification/standard Data:	80205-nas463 Professional/industrial Association Standard

How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463XKDD10M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.