

**Description**

Nut Length: 1-1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS463XKDD416H
Minimum Qty (MOQ):	25 EA
NSN:	5310-00-527-1427
Schedule B:	7616.10.1000
ECCN:	9A991



NO IMAGE  
AVAILABLE

## P/N NAS463XKDD416H Specifications

<b>Mounting Hole Diameter:</b>	0.102 Inches Minimum And 0.108 Inches Maximum
<b>Nut Style:</b>	Plate Nut Spacer
<b>Nut Length:</b>	1.281 Inches Nominal
<b>Thru-hole Diameter:</b>	0.322 Inches Minimum And 0.332 Inches Maximum
<b>Plate Thickness:</b>	0.090 Inches Nominal
<b>Plate Width:</b>	0.500 Inches Nominal
<b>Nut Mounting Provision:</b>	Countersunk Holes
<b>Mounting Provision Location:</b>	Nut Projection Side
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.497 Inches Minimum And 0.503 Inches Maximum
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	0.998 Inches Minimum And 1.002 Inches Maximum
<b>Mounting Hole Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 2014 Overall Or Aluminum Alloy 7075 Overall Or Aluminum Alloy 2024 Overall
<b>Material Document And Classification:</b>	Qq-a-255,t6 Fed Spec 1st Material Response Overall Or Qq-a-287,t6 Fed Spec 2nd Material Response Overall Or Qq-a-362,t3 Or T42 Fed Spec 3rd Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas463 Professional/industrial Association Standard

## How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463XKDD416H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.