

Description

Nut Length: 1-5/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS463Y10M
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-685-2277
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS463Y10M Specifications

Mounting Hole Diameter:	0.102 Inches Minimum And 0.108 Inches Maximum
Nut Style:	Plate Nut Spacer
Nut Length:	1.049 Inches Minimum And 1.079 Inches Maximum
Thru-hole Diameter:	0.260 Inches Minimum And 0.270 Inches Maximum
Plate Thickness:	0.027 Inches Minimum And 0.037 Inches Maximum
Plate Width:	0.391 Inches Minimum And 0.421 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.341 Inches Minimum And 0.347 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.310 Inches Minimum And 0.314 Inches Maximum
Material:	Steel Comp 1010 Overall Or Steel Comp 1020 Overall Or Steel Comp 1025 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	Aisi 1010 Assn Std 1st Material Response Overall Or Mil-s-7952 Mil Spec 2nd Material Response Overall Or Mil-s-18729 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall

How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463Y10M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.