

Description

Nut Length: 1-5/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS463YC10 |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5310-00-854-9383 |
| Schedule B: | 7318.16.0085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS463YC10 Specifications

| | |
|---|---|
| Mounting Hole Diameter: | 0.102 Inches Minimum And 0.108 Inches Maximum |
| Nut Style: | Plate Nut Spacer |
| Nut Length: | 1.049 Inches Minimum And 1.079 Inches Maximum |
| Thru-hole Diameter: | 0.260 Inches Minimum And 0.270 Inches Maximum |
| Plate Thickness: | 0.058 Inches Minimum And 0.068 Inches Maximum |
| Plate Width: | 0.391 Inches Minimum And 0.421 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.341 Inches Minimum And 0.347 Inches Maximum |
| Center To Center Distance Between Mounting Holes Along Length: | 0.310 Inches Minimum And 0.314 Inches Maximum |
| Material: | Steel Corrosion Resisting Overall Or Steel Comp 301 Overall Or Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall |
| Material Document And Classification: | Mil-s-6721 Mil Spec 1st Material Response Overall Or Mil-s-5059 Mil Spec 2nd Material Response Overall |
| Surface Treatment: | Passivate Overall |

How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463YC10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.