



Military-Fasteners.com

P/N NAS463YC10LG

Description

Nut Length: 1-1/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS463YC10LG
Minimum Qty (MOQ):	15 EA
NSN:	5310-01-529-4529
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS463YC10LG Specifications

Mounting Hole Diameter:	0.105 Inches Nominal
Nut Style:	Plate Nut Spacer
Nut Length:	1.064 Inches Nominal
Thru-hole Diameter:	0.260 Inches Minimum And 0.270 Inches Maximum
Plate Thickness:	0.016 Inches Nominal
Plate Width:	0.406 Inches Nominal
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.341 Inches Minimum And 0.347 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.312 Inches Nominal
End Item Identification:	Vertical Stabilizer
Special Features:	2 Coats Of Epoxy Primer
Material:	Steel Comp 321 Overall Or Steel Comp 347 Overall Or Steel Comp 302 Overall
Material Document And Classification:	Ams 5510 Assn Std 1st Material Response Overall Or Ams 5512 Assn Std 2nd Material Response Overall Or Ams 5516 Assn Std 3rd Material Response Overall
Surface Treatment:	Passivate Overall And Plastic Epoxy Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec 1st Treatment Response Overall And Mil-prf-85582 Mil Spec 2nd Treatment Response Overall Or Mil-prf-23377.mil-prf-23377ty0 Mil Spec 2nd Treatment Response Overall
Specification/standard Data:	80205 - Nas463 Professional/industrial Association Standard

How to Order

Order this nut spacer from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS463YC10LG> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.